

WESTERN STYLE DUMP BODIES



SLEEK CROSSMEMBERLESS BODY FEATURING A SMOOTH UNDERSTRUCTURE

DESIGNED FOR SAND, GRAVEL, ASPHALT AND RELATED CONSTRUCTION MATERIALS JOBS

AR 450 MATERIAL AVAILABLE UPON REQUEST






SAFETY PROP

Provides additional safety for use during routine service of empty dump body.



TAILGATE AIR CYLINDER

Standard 2.5" x 8" air cylinder operates tailgate from cab via electric or air switch.



MOUNTING SADDLE & HYDRAULIC TANK

Fabricated on-site with industry leading quality control standards.



HilArk Industries 20020 Interstate 30 Benton, AR 72019 Ph: (501) 316-4040 Fax: (501) 634-4141 www.hilark.com







CAB PROTECTOR

Features angle bracing for maximum strength. Options include 1/2, 3/4 & Full. Shown with optional integrated tarp mount.

> See dealer for mounting options and complete details

STANDARD HIGH STRENGTH GRADE 50 STEEL

PARKER HEAVY-DUTY TELESCOPING HYDRAULIC HOIST

1-15/16" x 13" cylinder pin is standard.

Authorized Distributor:



Custom lighting packages available.

Meets FMVS standards.



TAILGATE HINGE ASSEMBLY

Built of AR 450 steel hinge arms, 3/16" Hi-Tensile steel side plates, three case hardened bushings and a removable pin designed to grease all three bushings ensuring long life and easy service.



REAR HINGE AND REAR HINGE ASSEMBLY

Features doubled side plates, greaseable bushings and removable pins. Standard (shown) is 1-15/16" with 1/2" wall bushings. Heavy-Duty models available.



TAILGATE LATCH

Constructed with a 5/8" AR 450 steel latch arm, six greaseable pivot points. Provides easier access for assistance during routine maintenance